



Accent Manufacturing PTY (LTD)

Reg. 1999 2745107 VAT 4880187994
PO Box 745 Scottburgh 4180
South Africa
Tel +27 (0) 39 9761114
Fax +27 (0) 865357997
E-mail: gdenys@accentmanuf.com
Custom registration number: 1739697

Material Safety Data sheet

1. Chemical Product and Company Identification

1.1 Product: Putty Adhesive

1.2 Main usage: attaching posters to wall; cleaning fluff from clothes; holding frames straight etc.

1.3 Company: Accent Manufacturing PTY (LTD)

Reg. 1999 2745107 VAT 4880187994
PO Box 794 Scottburgh South Africa
Production facilities: 16 Payne Street Park Rynie South Africa
Tel +27 39 976 1114
Fax +27 85 535 7997 email gdenys@accentmanuf.com

1.4 In emergencies: tel + 27 823880713

2. Identification of danger

There are no immediate dangers for the environment or user of the product

3. Composition, Information on components

product composition

	CAS number	%
butyl rubber ; isobutylene copolymer	9003-29-6	7.4
hydrocarbon resin (escorez 1310)		0.8
polybutene	9003-29-6	0.7
calcium carbonate A	471-34-1	43.7
calcium carbonate B	471-34-1	21.5
precipitated calcium carbonate	471-34-1	21.5
white mineral oil	64742-55-8	3.0
resins	28514-92-3	0.7
Tioxide pigment (for white product only)	13463-67-7	0.7
		100.0

Product does not contain any solvents or toxic components

Product is non-toxic

PH: neutral

4. First Aid

Non-hazardous in case of contact with skin or inhalation
Ingestion: no health risks if small quantities are ingested

5. Fire explosion data:

Product is non-flammable
No special storage conditions are required
Auto ignition temperature: not applicable

6. Spill treatment

Not applicable

7. Handling and storage

Shelf life: indefinite (if kept in ambient temperatures)
Storage: avoid storage temperature above 45 degrees centigrade
No specific handling or storage precautions have to be taken

8. Exposure to product; protection

Exposure of product to hands, eyes, skin or inhaling does not create a risk or danger.

9. Chemical and physical properties

See paragraph 3

10. Stability and reactivity

Product is stable and non-corrosive
Good resistance to alcohols, poor to solvents and oils
Chemical resistance: good to mineral and organic acids, alkalis and salts.

11. Toxicologic information

Product is not toxic

12. Ecological information

Product does not create any pollution or environmental risk when disposed off.

13. Elimination

Not applicable

14. Transport

Custom tariff code: 3506-10

No specific precautions to be made. Product is not flammable and does not contain solvents

15. Test/Standards approved

FHSA 16 CFR toxicity risk assessment (TRA) Toy safety
USP 61/ASTM and EN 71 approved
REACH compliant ; REACH 1907/2006 94/62/CE HAP
EN 71.3 GPSD EN 71 part 1 ; 2 ; 3 -9

16 Other information:

Cleaning instruction

Remove as much as possible mechanically. Remove residue with mineral terps or lighter fuel.
For safety reason: keep away from children below age of 3

Aug 2019 (2)